

WL8-5827

■■■ · ■■■■588x475x267mm■■■■■500x400x220mm■ ■■■■■45+175mm ■■■■■■295mm

Specifications

|                   |                                                                    |
|-------------------|--------------------------------------------------------------------|
| SKU               | WL8-5827                                                           |
| Series            | ■■■                                                                |
| Material          | ■■■■■588x475x267mm■■■■■500x400x220mm■ ■■■■■45+175mm ■■■■■■295mm    |
| Outer dimensions  | (—)                                                                |
| Inner dimensions  | (—)                                                                |
| Wall thickness    |                                                                    |
| Weight            | 7.80 kg (17.20 lbs)                                                |
| IP rating         | IP54 (■■■■■)                                                       |
| Temperature range | −40°C ~ +80°C                                                      |
| Load capacity     | 15–30 kg                                                           |
| MOQ               | 500 pieces                                                         |
| Lead time         | 30–45 days after artwork approval                                  |
| Certificates      | CE / RoHS / REACH / ISO 9001:2015 / BSCI · MIL-STD-810H on request |
| Shipping          | EXW Guangdong or FOB Shenzhen / Ningbo                             |
| Last updated      | 2026-08-15                                                         |

OEM / ODM Customization

- Custom dimensions / Pantone color matching
- Logo: silk-screen, hot-stamp, laser engraving
- Foam: CNC-cut EVA / PU / PE, pick & pluck
- Hardware: wheels, trolley, pressure valve
- Packaging: standard export carton or custom

Specifications are typical. Final specs per confirmed drawing. EXW Guangdong or FOB Shenzhen / Ningbo.