

WL8-8442

■■■ · ■■■■843x592x415mm■■■■■740x518x364mm■ ■■■■■44+320mm ■■■■■295mm

Specifications

SKU	WL8-8442
Series	■■■
Material	■■■■■843x592x415mm■■■■■740x518x364mm■ ■■■■■44+320mm ■■■■■295mm
Outer dimensions	(—)
Inner dimensions	(—)
Wall thickness	
Weight	15.32 kg (33.77 lbs)
IP rating	IP54 (■■■■■)
Temperature range	−40°C ~ +80°C
Load capacity	15–30 kg
MOQ	500 pieces
Lead time	30–45 days after artwork approval
Certificates	CE / RoHS / REACH / ISO 9001:2015 / BSCI · MIL-STD-810H on request
Shipping	EXW Guangdong or FOB Shenzhen / Ningbo
Last updated	2026-08-15

OEM / ODM Customization

- Custom dimensions / Pantone color matching
- Logo: silk-screen, hot-stamp, laser engraving
- Foam: CNC-cut EVA / PU / PE, pick & pluck
- Hardware: wheels, trolley, pressure valve
- Packaging: standard export carton or custom

Specifications are typical. Final specs per confirmed drawing. EXW Guangdong or FOB Shenzhen / Ningbo.